


FITTING INSTRUCTIONS FOR EH0055BK / EXHAUST HANGER KAWASAKI NINJA 300 2013



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW. DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike.

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com







Picture 1 Picture 2

LEGEND

ITEM 1 = EXHAUST HANGER (EH0055) (x1).

ITEM $2 = M6 \times 20 \text{mm}$ LONG BUTTON HEAD BOLT (x1).

ITEM 3 = M6 WASHER (x1).

ITEM 4 = M6 NYLOC NUT (x1).

ITEM $5 = M8 \times 15 \text{mm}$ LONG BUTTON HEAD BOLT (x2).

ITEM $6 = M10 \times 25 \text{mm}$ LONG BUTTON HEAD BOLT (x1).

ITEM 7 = M10 WASHER (x1).

ITEM 8 = M10 NYLOC NUT (x1).

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

TOOLS REQUIRED

- Set of metric Allen keys to include 4, 5 & 6mm A/F sizes.
 - Socket set to include 10 & 14mm sockets & wrench.

FITTING INSTRUCTIONS

- Remove OEM rear foot pegs/exhaust hanger and un-bolt the rear brake reservoir from the hanger (do not disconnect any hoses and ensure the reservoir remains upright (it's a good idea to cable tie it to the frame temporarily, as shown in picture 2)).
- Place two M8 x 15mm long button head bolts (item 5) through the two top holes in the R&G hanger (item 1) and offer up to the bike as shown above. Engage the threads a couple of turns (do not tighten yet).
- Position the M10 x 1.25 x 25mm long button head bolt (item 6) through the lower hole of the exhaust hanger and then through the exhaust mount. Fit one M10 washer and nyloc nut to the exposed thread on the back and tighten all bolts evenly.
- Insert the M6 x 20mm bolt (item 2) through the exhaust hanger and then through the reservoir mounting hole, before fitting the M6 washer and M6 Nyloc nut on the exposed thread, as shown in picture 1 and tighten (ensure the hose is positioned behind the exhaust hanger).

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ



 Please ensure when the motorcycle is being used that no parts are in such a position that they may collide/damage other bike parts (this is particularly important if using after-market cans or exhaust systems).

Please note that it is your responsibility to ensure that no part of the exhaust hanger or exhaust assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.

ISSUE 1 21/11/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)




Instructions de montage FOR EH0055BK / Support pot d'échappement KAWASAKI NINJA 300 2013



<u>LE KIT CONTIENT LES ARTICLES EXPOSES CI-DESSOUS, VERIFIER QUE TOUTES LES PIECES SOIENT PRESENTES AVANT DE PROCEDER AU MONTAGE.</u>

LA FAÇON DONT LE KIT EST EMBALLE NE CORRESPOND PAS FORCEMENT A LA FAÇON DE MONTER LES PIECES SUR LA MOTO.

Notez que si les kits sont emballés avec des rondelles en caoutchouc servant à tenir les composants, ces rondelles doivent être jetées.



R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ







Photo 1 Photo 2

LEGENDE

ARTICLE 1 = Support pot d'échappement (EH0055) (x1).

ARTICLE $2 = M6 \times 20 \text{mm}$ Long boulon à tête ronde (x1).

ARTICLE 3 = M6 Rondelle (x1).

ARTICLE 4 = M6 Ecrou en Nyloc (x1).

ARTICLE $5 = M8 \times 15 \text{mm}$ Long boulon à tête ronde (x2).

ARTICLE $6 = M10 \times 25 \text{mm}$ Long boulon à tête ronde (x1).

ARTICLE 7 = M10 Rondelle (x1).

ARTICLE 8 = M10 Ecrou en Nyloc (x1).

NOTEZ QUE SI LES KITS SONT EMBALLES AVEC DES RONDELLES EN CAOUTCHOUC SERVANT A TENIR LES COMPOSANTS, CES RONDELLES DOIVENT ETRE JETEES.

Outils requis

- Clés Allen 4, 5 & 6mm
 - Clés 10 & 14mm

Instructions de montage:

- Enlever les repose pieds d'origine/le support de pot d'échappement et déboulonner le reservoir de frein arrière du support (Ne pas déconnecter des tuyaux et assurez vous que le réservoir reste debout (c'est une bonne idée d'attacher les câbles temporairement, comme le montre la photo 2)).
- Placer 2 boulons à tête ronde M8 x 15mm (Article 5) à travers les 2 trous supérieurs du support R&G (Article 1) et montez-le sur la moto comme indiqué ci dessus. Serrez à 2 tours (Ne pas bloquer pour le moment).
- Positionner le long boulon à tête ronde M10 x 1.25 x 25mm (Article 6) à travers le trou inférieur du support de pot d'échappement puis à travers le support d'échappement. Passer une rondelle M10 et un écrou en Nyloc sur le filetage et serrer les 4 boulons de façon égale.

R&G Racing



- Insérer le boulon à tête ronde M6 x 20mm à travers le support d'échappement puis à travers le support de réservoir, avant de passer une rondelle M6 et un écrou en Nyloc M6 sur le filetage (Photo 1) puis serrer (Assurez vous que le tuyau soit placé derrière le dispositif de suspension d'échappement).
- Assurez-vous qu'aucune partie n'entre en contact lorsque la moto sera en route. Cela pourrait créer des dommages à la moto. (Ce point est particulièrement important si vous utilisez des pots d'échappement qui ne sont pas d'origine).
- Il est de votre responsabilité de vous assurer qu'aucune partie de l'ensemble support de pot d'échappement n'entre en contact avec une autre partie de la moto. Ne pas prendre la route sans avoir fait ces vérifications. Compresser l'amortisseur arrière pour jauger de cet aspect par exemple.

ISSUE 1 21/11/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)



FITTING INSTRUCTIONS FOR BLP0026BK REAR FOOTREST BLANKING **PLATE**



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – the rubber washers should be thrown away!

TOOLS REQUIRED
4, 5 & 6mm A/F Allen key.

FITTING INSTRUCTIONS

- Remove rear footrest from left side of the bike.
- Fit the two counter-sunk head bolts through the holes in the blanking plate.
- Offer assembly up to bike and engage both bolts as shown in top picture.
- Tighten evenly.

ISSUE 1 21/11/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be **R&G** Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ



liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)



Instructions de montage pour BLP0026BK Plaque de protection repose pied arrière KAWASAKI NINJA 300 2013



LA FAÇON DONT LE KIT EST EMBALLE NE CORRESPOND PAS FORCEMENT A LA FAÇON DE MONTER LES PIECES SUR LA MOTO.

LES PIECES PRESENTEES PEUVENT N'ETRE QUE REPRESENTATIVES, AFIN DE FACILITER ET CLARIFIER LES INSTRUCTIONS DE MONTAGE.

NOTEZ QUE SI LES KITS SONT EMBALLES AVEC DES RONDELLES EN CAOUTCHOUC SERVANT A TENIR LES COMPOSANTS, CES RONDELLES DOIVENT ETRE JETEES.

Outils requis

• Clé Allen 4, 5 et 6mm

Instructions de montage:

- Enlever le repose pied du coté gauche de la moto.
- Passer les 2 boulons à tête fraisée à travers les trous dans la plaque de montage.
- Monter l'ensemble sur la moto et engager les 2 boulons (photo du haut).
- Serrer de façon égale.

•

ISSUE 1 21/11/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise

R&G Racing



than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)