



Fitting Instructions for RAD9015BK/TI

Radiator & Oil Cooler Guard Set Black - Suzuki GSXR1000 '07-'08


Included in this kit:

- 1x Radiator Guard
- 1x Oil Cooler Guard
- 2 x Cable/Zip Ties
- 2x Protective Foam Pads

- To fit the radiator guard to the bike use the foam pads provided and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator. The two cable ties go through the slots at the top of the radiator guard and around the mounting brackets of the radiator. At the bottom bolt the radiator guard to the original mounting brackets then once in position tighten all cable ties.

Fitting Instructions for Oil Cooler Guard

SUZUKI GSXR 1000 K5/K6 & K7/K8



In This Kit There Should Be

- 1x Oil Cooler Guard (OCG0001).
- 1x 100mm Lengths of self-adhesive Foam.
- 2x M6x25mm long button head bolts.
 - 2x M6 washers.

To fit to GSXR 1000 K7-K8

- Remove the original plastic oil cooler cover.
- To fit the oil cooler guard to the bike cut the foam strips provided into 10mm wide pieces and stick them to the back of the oil cooler guard, so that they sit between the oil cooler guard and the oil cooler itself.
- Fit the oil cooler guard as original using the two new bolts and washers from kit to secure the two top mountings and the original bolt and washers on the bottom mount.
- Refit the original plastic oil cooler cover as original.

To fit to GSXR 1000 K5-K6

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



Picture 1



Picture 2



Picture 3

- To fit the oil cooler guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the oil cooler guard frame, so that they sit between the oil cooler guard and the oil cooler.
- Remove the side fairings from both sides of the bike, along with the plastic grille behind the front wheel, as shown in pictures 1 & 2.
- Remove the three bolts that secure the oil cooler in place, two at the top and one on the bottom.
- Offer the R&G Oil Cooler Guard up to the oil cooler. The mounts on the oil cooler guard should align with those on the oil cooler.
- Re-fit the original bolt into the lower mount and use one of the M6 x 25mm long button head bolts supplied, along with one M6 washer, to locate through the mounting hole and into the oil cooler mount, as shown in picture 3.
- Ensure the oil cooler guard is correctly positioned before fully tightening the three bolts.

Issue 2 14/01/2014 (AR)

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



Instructions de montage de RAD9015BK/TI

Suzuki GSXR1000 '07-'08

Ce kit contient:

- 1x Protection de radiateur
- 1x Grille de protection refroidisseur d'huile
- 2 x Colliers de serrage
- 2 x Protections en mousse

- Pour fixer la protection de radiateur sur la moto, vous devez coller les 2 pads de mousse sur l'arrière de l'armature de la protection (de manière à ce qu'ils soient positionnés entre le radiateur et la protection R&G). Utiliser 4 colliers de serrage pour maintenir la protection sur la moto. (2 en haut et 2 en bas). Deux colliers de serrage seront à positionner sur les deux fixations supérieures de la protection et entoureront les pattes de maintien du radiateur sur la moto.
Pour la fixation du bas, fixer la protection en utilisant les vis et points de fixation de radiateur.

Instructions de montage Protection refroidisseur d'huile

SUZUKI GSXR 1000 K5/K6 & K7/K8



Le kit doit contenir :

- 1x Protection refroidisseur d'huile (OCG0001).
- 1x 100mm Mousse thermo rétractable.
- 2x M6x25mm Boulons.
- 2x M6 Rondelles.

Pour une installation sur un GSXR 1000 K7-K8 :

- Enlever la protection refroidisseur d'huile d'origine.
- Couper la mousse autocollante en bandeaux de 10mm de large et collez-les au bas du cadre protection de refroidisseur d'huile pour que les bandeaux soient placés entre la protection refroidisseur d'huile et le refroidisseur d'huile.
- Monter la protection refroidisseur d'huile comme à l'origine en utilisant les 2 nouveaux boulons et rondelles du kit pour fixer les 2 supports supérieurs et le boulon d'origine et rondelles sur le support du bas.
- Remettre la protection plastiques refroidisseur d'huile comme à l'origine.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



Pour une installation sur un GSXR 1000 K5-K6



Photo 1



Photo 2



Photo 3

- Couper la mousse autocollante en bandeaux de 10mm de large et collez les au bas du cadre protection de refroidisseur d'huile pour que les bandeaux soient placés entre la protection refroidisseur d'huile et le refroidisseur d'huile.
- Enlever les carénages latéraux des 2 cotés de la moto, avec la grille plastique derrière la roue avant (photos 1 & 2).
- Enlever les 3 boulons qui fixent le refroidisseur d'huile en place, 2 sur le haut et un au bas.
- Mettre la protection refroidisseur d'huile R&G sur le refroidisseur d'huile. Le supports sur la protection refroidisseur d'huile doivent s'aligner avec ceux du refroidisseur d'huile.
- Remettre le boulon d'origine dans le support inférieur et utiliser un des boulons M6 x 25mm fournis, avec une rondelle M6, pour le placer à travers le trou de fixation et dans le support refroidisseur d'huile (photo 3).

Veiller à ce que la protection refroidisseur d'huile soit correctement positionnée avant de serrer complètement les 3 boulons.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



Montageanleitung für den RAD9015BK/TI

Kühler- & Ölkühlerschutz Schwarz - Suzuki GSXR1000 '07-'08

Dieser Kit beinhaltet:

**1x Kühlerschutz
1 x Ölkühlerschutz
2 x Kabelbinder
2x Schaumstoff-Schutzstreifen**

- Um den Kühlerschutz am Motorrad zu montieren, zuerst Sie die mitgelieferten Schaumstoff-Schutzstreifen auf der Rückseite des Kühlerschutzrahmens kleben, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind. Die beiden Kabelbinder durch die Schlitze oben am Kühlerschutz einführen, dann um die Montagehalterungen des Kühlers wickeln. Den Kühlerschutz unten an den originalen Montagehalterungen anschrauben und anschließend alle Kabelbinder festziehen.
- Um den Ölkühlerschutz zu montieren, benutzen Sie die Originalmontagehalterungen für den Ölkühler und mit den Originalschrauben befestigen.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com